



tesa® Flooring Tape Extra Strong Hold

BNR 5670, 5671, 5672, 5681, 5686, 5687, 5690, 5691, 5692, 5696

tesa® Flooring Tape Extra Strong Hold is a double-sided flooring tape for the reliable fixation of carpets and PVC in indoor and covered outdoor areas.

Features

- Suitable for all carpets and PVC flooring
- Extra-strong double-sided adhesive
- Can also be used with underfloor heating and in damp rooms
- Easy to tear by hand

Consumer Product Properties

- | | | | |
|---------------------------|--|--------------------------|-----------|
| • Applicationfield | Home | • Reusable | no |
| • Tear resistant | yes | • Refillable | no |
| • Spare part service | no | • Recyclable | no |
| • Humidity resistant | yes | • Shape | Roll |
| • Resistance to chemicals | Yes | • Batteries required | no |
| • Solvent free | no | • Batteries included | no |
| • Suitable surfaces | Tiles, Glass, Plaster, Steel,
Stone, Brick, Acrylic glass,
Metal, Most plastics,
Paper, Cardboard | • Certified according to | DIN 18365 |

Consumer Technical Data

- | | | | |
|--------------------------|--------------------|--------------------------|--------|
| • Area of use | In- and Outdoor | • Total thickness | 240 µm |
| • Material | PP (polypropylene) | • Temperature resistant | yes |
| • Ecofriendly packaging | no | • Temperature resistance | °C |
| • Residue-free removable | no | • Temperature resistance | from |
| • Adhesive strength | Very high adhesion | • Temperature resistance | °C |
| • Type of adhesive | tackified acrylic | • up to | |
| • Tensile strength | 30 N/cm | • Tensibility | 20 % |
| | | • Hazard material | no |

tesa[®] Flooring Tape Extra Strong Hold

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=05670>