

# tesa® Flooring Tape Hook & Loop

BNR 56187, 56188

tesa® Flooring Tape Hook and Loop is especially suited for the removable fixation of fleece and felt-backed carpet even in damp rooms and with underfloor heating.

## Features

- Suitable for fleece- or felt-backed carpets
- For all hard, dry and clean surfaces
- Can also be used with underfloor heating and in damp rooms
- Allows easy replacement of carpets

## Consumer Product Properties

- |                           |      |                      |   |
|---------------------------|------|----------------------|---|
| • Applicationfield        | Home | • Suitable surfaces  | Tiles, Glass, Plaster, Steel, Stone, Brick, Acrylic glass, Metal, Most plastics, Paper, Cardboard |
| • Tear resistant          | yes  | • Recyclable         | no  |
| • Humidity resistant      | no   | • Shape              | Roll  |
| • Resistance to chemicals | No   | • Batteries required | no  |
| • Solvent free            | no   | • Batteries included | no  |

## Consumer Technical Data

- |                          |                    |                         |                  |
|--------------------------|--------------------|-------------------------|------------------|
| • Material               | PP (polypropylene) | • Type of adhesive      | synthetic rubber |
| • Ecofriendly packaging  | no                 | • Total thickness       | 1000 µm          |
| • Residue-free removable | no                 | • Temperature resistant | no               |
| • Adhesive strength      | High adhesion      |                         |                  |

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=56187>